

CARVER S.r.l. Unipersonale

Uffici commerciali e stabilimento:
Via Giovanni XXIII, 36 (zona industriale)
20090 Rodano (MI) - ITALY
Tel. +39 02 95 00 171
Fax +39 02 95 32 09 21
Website: www.carver.it
E-mail: info@carver.it



TECHNICAL DATASHEET

rev. 01 of 05/04/2016

PULIDECK (hardwood grey-remover)

code SO9000

TECHNICAL DATA

(with room temperature of +23°C and 65% of relative air humidity)

Appearance	Opalescent colourless liquid
Viscosity	25 ± 5 sec. F4
pH	2,5 ± 0,5
Specific weight	1,06 ± 0,02 Kg/l
Average yield of the product	10-20 m ² /l

DESCRIPTION

Water-based detergent for the cleaning and restoration of wooden items for outdoor use. The product removes dirt and grey patina that forms on the surface, restoring the wood original colour. After cleaning, the item can be treated with one of our products for outdoor protection (EXTEROL 050, COLORHIT, CARDECK, AQUANATUR, AQUACOLOR, AQUADECK). The product is ready-to-use.

STANDARD PACKAGING

4-litre plastic bucket.

DIRECTIONS

Apply the product on the item with a brush and wait for at least 15-20 minutes. Remove the surface patina with a semi-stiff brush or a Red Scotch-Brite pad. Rinse with water and allow to dry before treating the wood with a protective coating. The patina can also be removed with the help of a pressure washer.

NOTICE

- In case of high temperatures and low environmental humidity, it is advisable to perform a second spraying before starting with the brushing.
- The product might damage the surface of materials other than wood. In case of accidental contact, wash immediately with water.
- The use of rubber gloves and goggles is recommended while handling the product.

SAFETY INFORMATION

Ingredients (Reg. UE 648/2004)

Phosphates 5% ≤ C < 15%
Anionic surface-active agents 5% ≤ C < 15%
Perfumes <5%

The product is classified as dangerous according to Regulation EC 1272/2008 (CLP) and following modifications and updating. Consult the Safety Data Sheet, provided by law, to get more information.

PROTECT FROM FREEZING!

If the original unopened container is stored in a cool and dry place, the product will keep for at least 12 months.

N.B.: The information contained in this technical datasheet is to the best of our knowledge and experience. Since the conditions of use are beyond our control, no warranty is given or implied.